

BIFACIAL TOPCON MONOCRYSTALLINE • 144TNB10

Half-Cut DOUBLE GLASS



High Conversion Efficiency

High panel efficiency to guarantee high power output



Self-Cleaning And Anti-Reflection Glass

Coating glass for self-cleaning reduces surface dust



Outstanding Low Irradiation Glass

Outstanding panel performance even in weak light conditions



Excellent Durability

Wind load up to 2400 Pa, Snow load up to 5400 Pa




0~+5W Positive Power Tolerance



Easy Installation



Twice EVA Laminated Double Glass




30 Years Performance Warranty



12 Years Product Warranty

16BB
n-Type



CWT585-144TNB10 585 Wp

CWT590-144TNB10 590 Wp

CWT595-144TNB10 595 Wp

CWT600-144TNB10 600 Wp

CWT605-144TNB10 605 Wp



IEC 61215, IEC 61730-1, IEC 61730-2
IEC 62804 PID (POTENTIAL INDUCED DEGRADATION)
ISO 9001:2015, ISO 14001:2015, ISO 45001:2018

BIFACIAL TOPCON MONOCRYSTALLINE 144TNB10 **Half-Cut**

ELECTRICAL CHARACTERISTICS

Model Type	CWT585 144TNB10	CWT590 144TNB10	CWT595 144TNB10	CWT600 144TNB10	CWT605 144TNB10
Peak Power (Pmax)	585 Wp	590 Wp	595 Wp	600 Wp	605 Wp
Module Efficiency	22.65	22.84	23.03	23.22	23.41
Maximum Power Voltage (Vmp)	43.15	43.35	43.55	43.75	43.95
Maximum Power Current (Imp)	13.56	13.62	13.67	13.72	13.77
Open Circuit Voltage (Voc)	51.18	51.38	51.58	51.78	51.98
Short Circuit Current (Isc)	14.38	14.45	14.53	14.60	14.68
Power Tolerance	0~+5W				
Maximum System Voltage	1500V DC				
Operating Temperature	-40 ~ +85°C				
Protection Class	Class II				
Maximum Series Fuse Rating	25A				

MECHANICAL SPECIFICATIONS

Cell Dimensions(mm)	182 x 91
Cells per Module(pcs)	144 (6x24)
Weight(kg)	33.0
Panel Dimensions(mm)	2278x1134x35
Max. Wind/Snow Load(Pa)	2400/5400
Junction Box	IP68
Junction Box Cable Length(mm)	300-1600
Glass Thickness (mm)	2.0 / 2.0

REAR SIDE POWER GAIN

(590W Front Power Referenced)

Rear Power Gain	5%	10%	15%	20%	25%
Maximum Power (Pmax)	619.50	649.00	678.50	708.00	737.50
Short Circuit Current (Isc)	15.17	15.90	16.62	17.34	18.06
Open Circuit Voltage (Voc)	51.38	51.38	51.38	51.38	51.38
Maximum Power Current (Imp)	14.30	14.98	15.66	16.34	17.03
Maximum Power Voltage (Vmp)	43.35	43.35	43.35	43.35	43.35


TEMPERATURE CHARACTERISTICS

Temp. Coeff. of (Isc)	0.040%/°C
Temp. Coeff. of (Voc)	-0.260%/°C
Temp. Coeff. of (Pmax)	-0.30%/°C


PACKING CONFIGURATION

Container	40' GP
Pieces Per Pallet	31
Pieces Per Container	620
Pallet Per Container	20

PHYSICAL CHARACTERISTICS



ELECTRICAL CHARACTERISTICS



* The specifications are obtained under the standard test conditions: 1000W/m2 solar irradiance, 1.5 Air Mass and cell temperature of 25°C. Measurement uncertainty for all panels is 3%. The actual transactions will be subject to the contracts. These parameters are for reference only and it is not a part of the contracts. The technical specifications in this document may vary. For more information, refer to the "Installation Manual".

* For roof, facades and installations on similar surfaces, solar panels should be mounted over a fire-resistant covering suitable for this application, with adequate ventilation between the back of the solar panels and the mounting surface. Improper installations are hazardous and may spark a fire. Solar panels must not be mounted on structures and roofs which are made of not fire-resistant materials such as plastic layer, transparent plastic, PVC or similar materials without any fire-protection layer. Usage and installation not in accordance with the guidelines as outlined in the installation manual will terminate the warranty. Please refer to the installation manual and the warranty documents for further details.

* CW Enerji reserves the right to change the specification of products without prior notice.

Ver.2501.30