

BIFACIAL PERC MONOKRISTALLINE • 132PMB12

Half Cut

DOUBLE GLASS



High Conversion Efficiency

High panel efficiency to guarantee high power output



Self-Cleaning And Anti-Reflection Glass

Coating glass for self-cleaning reduces surface dust



Outstanding Low Irradiation Glass

Outstanding panel performance even in weak light conditions



Excellent Durability

Wind load up to 2400 Pa, Snow load up to 5400 Pa




0~+5W Positive Power Tolerance



Easy Installation



Twice EVA Laminated Double Glass



CWT675-132PM12 675 Wp


CWT670-132PM12 670 Wp

CWT665-132PM12 665 Wp

CWT660-132PM12 660 Wp

CWT655-132PM12 655 Wp

CWT650-132PM12 650 Wp



30 Years Performance Warranty



12 Years Product Warranty



IEC 61215, IEC 61730-1, IEC 61730-2
IEC 62804 PID (POTENTIAL INDUCED DEGRADATION)
IEC 61701 SALT MIST CORROSION
IEC 62716 AMMONIA CORROSION
ISO 9001:2015, ISO 14001:2015, ISO 45001:2018

BIFACIAL PERC MONOKRISTALLINE • 132PMB12 Half-Cut


ELECTRICAL CHARACTERISTICS

Model Type	CWT650 132PM12	CWT655 132PM12	CWT660 132PM12	CWT665 132PM12	CWT670 132PM12	CWT675 132PMB12
Peak Power (Pmax)	650 Wp	655Wp	660Wp	665Wp	670Wp	675Wp
Module Efficiency	20.92	21.09	21.25	21.41	21.57	21.73
Maximum Power Voltage (Vmp)	37.50	37.70	37.90	38.10	38.30	38.50
Maximum Power Current (Imp)	17.34	17.38	17.42	17.46	17.50	17.54
Open Circuit Voltage (Voc)	45.20	45.40	45.60	45.80	46.00	46.20
Short Circuit Current (Isc)	18.35	18.39	18.44	18.48	18.51	18.56
Power Tolerance	0~+5W					
Maximum System Voltage	1500V DC					
Operating Temperature	-40 ~ +85°C					
Protection Class	Class II					
Maximum Series Fuse Rating	30A					

MECHANICAL SPECIFICATIONS

Cell Dimensions(mm)	210x105
Cells per Module(pcs)	132 (6x22)
Weight(kg)	39.5
Panel Dimensions(mm)	2384x1303x35
Max. Wind/Snow Load(Pa)	2400/5400
Junction Box	IP68
Junction Box Cable Length(mm)	350-1600
Glass Thickness (mm)	2.0 / 2.0

PHYSICAL CHARACTERISTICS



TEMPERATURE CHARACTERISTICS

(660W Front Power Referenced)

Rear Side Power Gain	5%	10%	15%	20%	25%
Peak Power (Pmax)	693	726	759	792	825
Short Circuit Current (Isc)	19.28	20.24	21.05	21.96	22.82
Open Circuit Voltage (Voc)	45.60	45.60	45.80	45.80	45.80
Maximum Power Current (Imp)	18.19	19.06	19.82	20.68	21.54
Maximum Power Voltage (Vmp)	38.10	38.10	38.30	38.30	38.30


TEMPERATURE CHARACTERISTICS

Temp. Coeff. of (Isc)	0.040%/°C
Temp. Coeff. of (Voc)	-0.260%/°C
Temp. Coeff. of (Pmax)	-0.340%/°C

PACKING CONFIGURATION

Container	40' GP
Pieces per Pallet	31
Pieces Per Container	527
Pallet Per Container	17

ELECTRICAL CHARACTERISTICS



* The specifications are obtained under the standard test conditions: 1000W/m2 solar irradiance, 1.5 Air Mass and cell temperature of 25°C. Measurement uncertainty for all panels is 3%. The actual transactions will be subject to the contracts. These parameters are for reference only and it is not a part of the contracts. The technical specifications in this document may vary. For more information, refer to the "Installation Manual".

* For roof, facades and installations on similar surfaces, solar panels should be mounted over a fire-resistant covering suitable for this application, with adequate ventilation between the back of the solar panels and the mounting surface. Improper installations are hazardous and may spark a fire. Solar panels must not be mounted on structures and roofs which are made of not fire-resistant materials such as plastic layer, transparent plastic, PVC or similar materials without any fire-protection layer. Usage and installation not in accordance with the guidelines as outlined in the installation manual will terminate the warranty. Please refer to the installation manual and the warranty documents for further details.

* CW Enerji reserves the right to change the specification of products without prior notice.

Ver.2401.03